

Nylon Safety Netting



881010 100m (328') roll

881012 10m (33') bag

CLIP Bag of 50 plastic ring clips

- Reinforced top and bottom selvages
- For a professional, easy installation, use netting clips (one bag of 50 clips for each 5' of netting installed)
- UV-resistant nylon
- 1.6" (40mm) diamond-shaped mesh
- Knotless construction
- For installations from 12" to 28" high (30-71cm)

Installation

- 1) Select one of the attachment methods listed.
- 2) Do not cut the netting before you have completed the installation.
- 3) Begin at one end and attach the top, preferably with one attachment
- 4) Attach the bottom.
- 5) Secure one end, then the other.
- 6) Cut off the excess netting, preferably with a heat cut made with a rope knife, butane torch, or lighter. A knife or scissors can also be used.

Attachment Methods

- plastic ring clips – see **CLIP** above
- nylon cable ties
- utility line (1/16" or 3-4mm diameter)
- lifeline threading

How to Measure

- 1) Determine the height of your installation.
 - 2) Select the appropriate multiplier from the chart at right.
 - 3) Multiply the length of your installation by the multiplier.
 - 4) Add 10% for error.
- Example: Installation is 19'H x 22'L.
 Multiply 22' x 1.2=26.4' + 2.6' (10%)= 29'.
 Purchase 29' of netting.

Safety Netting Length Calculator

Height of Installation	Multiply By
12-16" (31-41cm)	1.1
18-20" (46-51cm)	1.2
22" (56cm)	1.3
24" (61cm)	1.4
26" (66cm)	1.5
28" (71cm)	1.7