



Stanchion Bases



Model	Construction	Shape	Inclination
97430	Aluminum	Triangle	0°
97442	Stainless	Triangle	0°
97440	Stainless	Triangle	5°
97439	Stainless	Square	0°
97441	Stainless	Square	5°

1" Stainless Steel Stanchions



Tapered



Spherical

Tapered tip model	Spherical tip model	Description*	Overall Height	Lifeline-to-tip Distance
97443	93633	1 lifeline hole	17.75" (45cm)	-
97445	93634	1 lifeline hole 0 mounting holes	17.75" (45cm)	-
97444	93635	2 lifeline holes	17.75" (45cm)	8.875" (22.5cm)
105505	105897	2 lifeline holes	24.1" (61cm)	12.1" (30.5cm)
105470	93637	2 lifeline holes†	24.75" (63cm)	12" (30cm)
105786	93638	2 lifeline holes 0 mounting holes	24.75" (63cm)	12" (30cm)
105787	105898	2 lifeline holes	26.75" (68cm)	12" (30cm)
97449	-	2 lifeline holes	29.5" (75cm)	14.4" (36cm)

* Except where noted, all stanchions have a single mounting hole drilled perpendicular to the lifeline hole(s), through a single wall of the stanchion, at 1.4" (35mm) above the base.

† Models 105470 and 93637 have an additional mounting hole drilled parallel to the lifeline holes, through both walls of the stanchion, at 1.8" (45mm) above the base.

Stanchion Gates



97451 Gate Stanchion

105789 Gate Door

- Can be used with any Goïot stanchion
- Designed to accommodate two lifelines
- Gates are 24.6" (61.5cm) high
- Distance between lifeline holes is 11.4" (28.5cm)
- Distance between leg fastening holes at base is 11.2" (28cm)